

**SENSIT<sup>®</sup> HXG-3P**  
COMBUSTIBLE GAS LEAK DETECTOR



Quickly find gas leaks with **SENSIT HXG-3P**

EU VERSION

**MADE IN THE USA**  
WITH GLOBALLY SOURCED COMPONENTS

**SENSIT**  
Technologies

Innovative Detection Solutions

[www.gasleaksensors.com](http://www.gasleaksensors.com)

# SENSIT<sup>®</sup> HXG-3P

Simultaneously displays LEL and PPM readings for accurate leak detection and analysis.

**SENSIT<sup>®</sup> HXG-3P** is an advanced, instrument used for detecting and finding the source of gas leaks.

**SENSIT<sup>®</sup> HXG-3P** measures combustible gases such as methane, propane, natural gas, pentane and other volatile organic compounds (VOCs).

The backlit LCD display shows percent lower explosive limit (LEL) and part-per million (ppm) readings simultaneously. Audible and visual alarms warn of potential hazardous conditions.

**SENSIT<sup>®</sup> HXG-3P** also features our unique audible tick control that helps find the source of gas leaks fast. The tick can be easily heard through the speaker located in the back of the instrument.

**SENSIT<sup>®</sup> HXG-3P** is

- Accurate
- Durable
- Easy to Use
- Easy to Maintain

**Find Gas Leaks Fast!**



## Standard Features

- Intrinsically Safe Design (Certified)
- Displays LEL and PPM
- Audible/Visual Alarms
- Infrared Downloading
- Long-life, Low-Cost Sensor
- Simple Calibration



## Applications

- Locate Small Gas Leaks
- Area Monitoring
- Gas Leak Surveying
- Arson / Accelerant Detection



## Partial List of Gases Detected

- |                  |            |
|------------------|------------|
| • Acetone        | • Alcohol  |
| • Ammonia        | • Butane   |
| • Gasoline       | • Halon    |
| • Hydrogen       | • Jet Fuel |
| • Ethylene Oxide | • Methane  |
| • Natural Gas    | • Propane  |
| • Refrigerants   | • Solvents |



**TO OPERATE:**

- 1. Press Power**
- 2. Wait 45 Seconds for Automatic Zeroing**
- 3. Begin to Use**

Patented

### SENSOR SPECIFICATIONS

TYPE	RESOLUTION	RANGE	ACCURACY
LEL	0.1%	0-100% LEL	±10%
PPM*	1 or 10ppm	0-50,000 ppm	±10%

\*PPM Optional

### PRODUCT SPECIFICATIONS

Size:	11.5" x 3" x 2.23" (292 x 7.6 x 6.9 cm)
Weight:	1.2 lb. (0.54 kg)
Operational Temp:	-4 to 104 F (-20 to 40° C)
Battery Life:	Alkaline: Approximately 12 hrs. Continuous



#### STANDARD KIT

Hard Carrying Case  
3 "C" Batteries  
Extra Sensor Cap  
Wrist Strap  
Instruction Manual

#### KIT OPTIONS

Optional PPM  
Probe Assembly  
Printer  
PC Interface  
Calibration Kit

CE Ex II 3 G

EEx ic IIB T3  
ATEX File No. NA45026-01X

## SENSIT® HXG-3P Instrument (With Pump)

SENSIT HXG-3P (With Pump)  
Part # 907-00000-08

## SENSIT® HXG-3P Standard Kit Replacement Parts

Sensor EX (LEL) (2611 Silver 4 Prong)  
Part # 375-2611-01

Sensor Cap (Replacement) w/"O" Rings  
Part # 870-00018

Hard Carrying Case  
Part # 872-00001

Wrist Strap  
Part # 360-00040

Instruction Manual  
Part # 750-00027

## SENSIT® HXG-3P Manual Calibration Kits

Methane Calibration Kit (21 liter 2.5% Methane)  
Part # 881-00016

Pentane Calibration Kit (34 liter 50% Pentane)  
Part # 881-00067

## SENSIT® HXG-3/3P Replacement Cylinders

2.5% Methane/Air (21 Liter)  
Part # 315-080012

2.5% Methane/Air (221 Liter)  
Part # 315-180013

Pentane (50% LEL) (34 Liter)  
Part # 315-100003



851 Transport Drive  
Valparaiso, IN 46383-8432

Phone: 888 4SENSIT  
888 473 6748  
219 465 2700

Fax: 219 465 2701  
[www.gasleaksensors.com](http://www.gasleaksensors.com)

**MADE IN THE USA**  
WITH GLOBALLY SOURCED COMPONENTS

SENSIT Technologies  
is in compliance with ISO 9001:2008



Distributed by:

