

SENSIT[®] RLD-2

REFRIGERANT GAS LEAK DETECTOR



SENSIT[®] RLD-2
makes leak detection quick and easy!

MADE IN USA



Innovative Detection Solutions

www.gasleaksensors.com



- SENSOR
- ON / OFF SWITCH
- ALARM LEDs
- TICK ADJUST
- EARPHONE JACK
- FLEXIBLE GOOSENECK
- BATTERY COMPARTMENT

- TO OPERATE:**
1. Power On
 2. Wait 30 Seconds
 3. Adjust Tick
 4. Begin to Use

SENSIT[®] RLD-2

REFRIGERANT GAS LEAK DETECTOR

SENSIT[®] RLD-2 Automatically detects all existing refrigerants and blends, including 404A.

EASY TO USE - High and low sensitivity settings and one hand operation makes leak detection quick and easy.

NO ADJUSTMENTS - Detects all existing refrigerant with no adjustments necessary to select and detect different refrigerants.

RLD-2 STANDARD FEATURES

- Long battery life
- Long sensor life
- Adjustable tick rate system
- Audible and Visual Indicators
- SENSIT[®] quality and durability



STANDARD KIT

- Soft Carrying Pouch
- 3 "C" Batteries
- Instruction Manual

PARTIAL LIST OF GASES SENSED*

CFS's	R-11	R-123
HCFC's	R-12	R-125
HFC's	R-22	R-134a
SF6	R-113	R-500
Ethylene Oxide	R-114	R-502

*Contact Sensit Technologies for more info.

PRODUCT SPECIFICATIONS

- Sensitivity: 1/2 oz. Year R-134a
- Size: 3.5" x 10" x 1.6" (8.9 x 25.4 x 4 cm)
- Weight: 1.3 pounds (0.59 kg)
- Operational Temp: 0 to 104° F (17.7 to 40° C)
- Battery Life: Alkaline: Approximately 8 hrs. Continuous



851 Transport Drive
Valparaiso, IN 46383-8432

Phone: 888 4SENSIT
888 473 6748
219 465 2700

Fax: 219 465 2701
www.gasleaksensors.com

MADE IN USA

SENSIT Technologies
is in compliance with ISO 9001:2008



Distributed by:

