

**EU VERSION** 



**Innovative Detection Solutions** 

www.gasleaksensors.com

MADE IN THE USA

# SENS T<sup>®</sup> HXG-3/3P

# Simultaneously displays LEL and PPM readings for accurate leak detection and analysis.

**SENSIT**<sup>®</sup> **HXG-3** is an advanced, instrument used for detecting and finding the source of gas leaks.

**SENSIT® HXG-3** measures combustible gases such as methane, propane, natural gas, pentane and other volatile organic compounds (VOCs).

The backlit LCD display shows percent lower explosive limit (LEL) and part-per million (ppm) readings simultaneously. Audible and visual alarms warn of potential hazardous conditions.

**SENSIT® HXG-3** also features our unique audible tick control that helps find the source of gas leaks fast. The tick can be easily heard through the speaker located in the back of the instrument.

SENSIT® HXG-3 is

- Accurate
- Durable
- Easy to Use
- Easy to Maintain

# Find Gas Leaks Fast!

# READY LOW

# Standard Features

- Intrinsically Safe Design (Certified)
- Displays LEL and PPM
- Audible/Visual Alarms
- Infrared Downloading
- Long-life, Low-Cost Sensor
- Simple Calibration



# **Applications**

- Locate Small Gas Leaks
- Area Monitoring
- Gas Leak Surveying
- Arson / Accelerant Detection



# **Partial List of Gases Detected**

- Acetone
- Ammonia
- Gasoline
- Hydrogen
- Ethylene Oxide Natural Gas
- Refrigerants
- Alcohol Butane
- Halon
- Jet Fuel
- Methane
- Propane
- Solvents



# **SENSOR SPECIFICATIONS**

| ТҮРЕ          | RESOLUTION | RANGE        | ACCURACY |
|---------------|------------|--------------|----------|
| LEL           | 0.1%       | 0-100% LEL   | ±10%     |
| PPM*          | 1 or 10ppm | 0-50,000 ppm | ±10%     |
| *PPM Optional |            |              |          |

# **PRODUCT SPECIFICATIONS**

| Size:             | 11.5" x 3" x 2.23" (292 x 7.6 x 6.9 cm)    |
|-------------------|--|
| Weight:           | 1.2 lb. (0.54 kg)                          |
| Operational Temp: | -4 to 104 F (-20 to 40° C)                 |
| Battery Life:     | Alkaline: Approximately 25 hrs. Continuous |



# **STANDARD KIT**

# Hard Carrying Case 3 "C" Batteries Wrist Strap

## **KIT OPTIONS**

Optional PPM Probe Assembly Printer Instruction Manual PC Interface Calibration Kit

# **OPTIONAL FEATURES**

Internal Pump (HXG-3P): Provides Faster Response Provides Better Sensor Protection



# **€** € 🖾 || 3 G EEx ic IIB T3 ATEX File No. NA45026-01X

# SENSIT<sup>®</sup> HXG-3 Instrument (No Pump)

SENSIT HXG-3 (No Pump) Part # 907-00000-02

### SENSIT® HXG-3 Standard Kit Replacement Parts

Sensor EX (LEL) (2611 Silver 4 Prong) Part # 375-2611-01

Sensor Cap Part # 365-00045

Hard Carrying Case Part # 872-00001

Wrist Strap Part # 360-00040

Instruction Manual Part # 750-00023

# SENSIT<sup>®</sup> HXG-3P Instrument (With Pump)

SENSIT HXG-3P (With Pump) Part # 907-00000-08

### SENSIT® HXG-3P Standard Kit Replacement Parts

Sensor EX (LEL) (2611 Silver 4 Prong) Part # 375-2611-01

Sensor Cap (Replacement) w/"O" Rings Part # 870-00018

Hard Carrying Case Part # 872-00001

Wrist Strap Part # 360-00040

Instruction Manual Part # 750-00027

# SENSIT<sup>®</sup> HXG-3 Manual Calibration Kits

Methane Calibration Kit (21 liter 2.5% Methane) Part # 881-00015

Pentane Calibration Kit (34 liter 50% Pentane) Part # 881-00077

# SENSIT® HXG-3P Manual Calibration Kits

Methane Calibration Kit (21 liter 2.5% Methane) Part # 881-00016

Pentane Calibration Kit (34 liter 50% Pentane) Part # 881-00067

### SENSIT<sup>®</sup> HXG-3/3P Replacement Cylinders

2.5% Methane/Air (21 Liter) Part # 315-080012

2.5% Methane/Air (221 Liter) Part # 315-180013

Pentane (50% LEL) (34 Liter) Part # 315-100003



851 Transport Drive Valparaiso, IN 46383-8432

Phone: 888 4SENSIT 888 473 6748 219 465 2700

Fax: 219 465 2701 www.gasleaksensors.com



SENSIT Technologies is an ISO 9001:2015 certified company.





### Distributed by: