

SENSIT® GOLD

MULTI-GAS DETECTION INSTRUMENT



Find Gas Leaks Fast
Durable and Low Cost Operation
Operation and Calibration Memory
Long Life Sensors
Monitor Hazardous Gas Conditions



DESIGNED TO HELP YOU FIND THE SOURCE OF COMBUSTIBLE GASES FAST!

Flexible Gooseneck

Backlit LCD Display

Alarm LEDs

BUTTON OPERATION

- A** Power and Mute Features and Exit Menu Items
- B** Enter, Change and Select Menu Items
- C** Save Data, Zero Sensors, Scroll/Change Menu Items

ADDITIONAL

SIZE
11.5" x 3" x 2.32" (292 x 76 x 59 mm)
WEIGHT
1.2 lbs. (544 g)
OPERATIONAL TEMP
0 to 120°F (-17.8 to 48.8°C)
STORAGE TEMP
-20 to 132°F (-28.9 to 55.6°C)
BATTERY LIFE
Alkaline: 12 hrs. continuous

Battery Compartment

Battery pack can be charged both while installed in the instrument or standalone

Luer Probe Connector

Water/Dirt Filter

LEL/PPM Sensor

TYPE	RANGE	ACCURACY
LEAK (CSA)	50-50,000 ppm	N/A
LEAK (UL)	10-50,000 ppm	N/A
PPM (CSA)	0-2,000 ppm	±10%
PPM (UL)	0-2,000 ppm	±10%
LEL	0-100% LEL	±10%
O ₂	0-25%	±0.2% or 10%
CO	0-2,000ppm	±5ppm or 5%
H ₂ S	0-100ppm	±2ppm or 5%
HCN	0-30ppm	±1ppm or 5%

Infrared Communications

Tick Adjust

Assist in pinpointing small combustible gas leaks with audible ticking tone

OPTIONAL FEATURES

DATA LOGGING

ADJUSTABLE ALARMS

Where the PPM scale is needed with low alarm

INFRARED PRINTER COMPATIBILITY

Puts instrument in low-power mode for quick use

ADDITIONAL FEATURES

Calibration Due Reminder